

High-performance FTIR Analyser for Mid-IR measurements



Innovative Design

- Rugged Construction
- Double Pivot Michelson Interferometer (patent pending)
- Small Footprint (0.1 m² ; 1.3 ft²)
- Compatible with most FTIR accessories
- Maintenance Free

Intuitive Software

- Easy to Use
- Efficient Data Acquisition, Processing and Analysis
- Extensive Built-In Health Monitoring

SPECTROSCOPIC PERFORMANCE (typical, at 25 °Celsius with DTGS detector)

■ Spectral Range	485 to 8,500 cm^{-1}
■ Resolution better than	0.7 cm^{-1}
■ Apodized Resolution Adjustable	1 to 64 cm^{-1} , in steps of 2x
■ Maximum Signal to Noise RMS (60 s, 4 cm^{-1} , at peak response)	50,000: 1
■ Signal Sampling	24-bit ADC
■ Short-term Stability	< 0.09 %
■ Temperature Stability	< 1 % per degree Celsius
■ Frequency Repeatability	(@ 1918 cm^{-1}) < 0.001 cm^{-1}
■ Frequency Accuracy	(@ 1918 cm^{-1}) < 0.01 cm^{-1}

APPLICATION SOFTWARE (Computer not included)

■ Standard Software	HORIZON MB™ FTIR Software
■ Operating System Compatibility	Win XP Pro
■ Optional Modules	Professional, Quantify, Library, Security, Scripting

OPTICAL BENCH

■ Beamsplitter Material	ZnSe (non-hygroscopic)
■ Interferometer Mechanism (patent pending)	High-throughput double pivot Michelson, fully jacketed
■ Purgeable	Enclosure, detector head & sample compartment
■ Source (with electronic stabilization)	(Ceramic Globar) 10-year expected life
■ Solid-state Laser	No scheduled maintenance required
■ Detector Module	DTGS
■ Sample Compartment Configuration	Open (Arid-Zone), center focus
■ Sample Compartment Dimensions	20 cm x 14 cm plate, 8.7 cm beam height
■ Sample Compartment Mounting	3-point pin-in-place mounts

DATA COMMUNICATIONS

■ Hardware	Port Ethernet, 10/100 Mbps
■ Connection	Direct-connect or LAN

INSTRUMENT ENCLOSURE

■ Material	Rugged Design, all-metal frame with integral handles
■ Size	435 mm (W) x 280 mm (D) x 372 mm (H)
■ Weight	24 kg

ENVIRONMENTAL

■ Universal Power Supply	120-240 VAC, 50/60 Hz
■ Power Consumption	65 W GH
■ Operating Temperature	10 °C to 35 °C
■ Operating Relative Humidity	5 % to 80 %, non-condensing
■ Regulatory Certification and Compliance	TUV and CE



ABB

Analytical Business Unit

Phone: +1 418-877-2944
 1 800 858-3847 (North America)
 E-mail: ftir@ca.abb.com
 Web: www.abb.com/analytical
www.mb3000ftir.com

MB3000 Specs B4480 2008-09

Copyright © 2008 by ABB Inc. All rights to trademarks reside with their respective owners. Specifications subject to change without notice. Pictures, schematics and other graphics contained herein are published for illustration purposes only and do not represent product configurations or functionality. User documentation accompanying the product is the exclusive source for functionality descriptions.